

Description

Field of the Invention

[0001] This invention relates to a hybrid-driven device with a battery and a fuel cell as power sources of a drive motor for mobile devices such as vehicles and watercrafts, or the like.

Background Art

[0002] A hybrid type electric car has been developed for the purpose of reducing pollution due to vehicles, in which an electric motor is used for driving the vehicle, and two kinds of batteries for constant speed running and high output running are combined as power sources of the vehicle to increase travel distance per one charge and to provide efficient and stable power supply during constant speed running and high output running such as acceleration. In such a hybrid-driven vehicle, a system has been contemplated in which methanol is used as primary fuel, and a fuel cell is used as a power supply source, including a reformer and a shift reactor for processing carbon monoxide, and a secondary battery (battery) is combined in addition to the power supply source, such as a lead battery for carrying peak load. In such a hybrid-driven vehicle, a vehicle controller is provided for drivingly controlling the motor in an optimum condition by supplying electric power efficiently in response to the operating conditions after switching-on of the power source. Modules constituting equipment such as a motor, a fuel cell and a battery are provided with sensors for detecting data, such as temperature, rpm or a state of the voltage and current, corresponding to the modules necessary for drive control of the vehicle, respectively, and the vehicle controller calculates required electric power or expected travel distance according to the detected output, for charging/discharging of the battery and the fuel cell, and drive control of the motor, or the like.

[0003] In constituting such a control system, it is desirable for each module to be easy in installation to the vehicle and maintenance so as to provide easy parts replacement including that of related control system parts, for improved application of modules, and also to receive reliable control data, for higher reliability of the control.

[0004] In driving a vehicle using two power sources of a battery and a fuel cell described above, the vehicle controller calculates expected travel distance from the data on the residual amount of power source capacities and fuel in the normal operating conditions of both power sources, makes an effective use of the power sources during running while verifying reliable travel to the destination, and makes proper use of the power sources, such as supplementary use of the battery to the delayed output response of the fuel cell during acceleration, so as to perform drive control of power sources through

their controllers, for constant stable running.

[0005] However, in case of abnormality in the battery or the fuel cell, continuous use of the power sources might disable drive control based on the data from the power source controller, preventing stable running, and the abnormal state might expand more widely due to delayed measures against the abnormality, causing damage to other sections.

[0006] In view of the foregoing, it is a first object of this invention to provide a hybrid-driven device capable of effecting improved efficiency of assembling work and maintainability of modules including a power system such as a motor and power supply sources such as a fuel cell and a battery, as well as reliable control.

[0007] In addition, it is a second object of this invention to provide a hybrid-driven mobile body in which the states of two power sources are detected during operation to calculate expected travel distance based on the detection data, and the states of power sources are grasped constantly during operation such that the mobile body is able to travel smoothly to the destination.

[0008] Further, it is a third object of this invention to provide a hybrid-driven device in which in the event that abnormality is detected in either of the two hybrid drive power sources, the use of the power source is stopped promptly to prevent expansion of the abnormal state so as to cope with the abnormality immediately, and operation is continued using the other power source, for smooth drive control of the power system.

Disclosure of the Invention

[0009] In order to achieve the foregoing first object, this invention may provide a hybrid-driven device having a first and a second power supply source as power sources for a power system for driving the device, a main switch for switching on the power sources, and a device controller for controlling the device, wherein said power system and said first and second power supply sources are arranged as module units, respectively, each module unit is provided with a module controller and detection means for detecting the state of the module, and said module controller has storage means for storing detected state data.

[0010] In this arrangement, equipment (modules) constituting the power system such as a motor, the first power supply source such as a fuel cell and the second power supply source such as a battery, are arranged as module units such as a motor unit, a fuel cell unit and a battery unit, respectively, to be combined integrally together with related equipment and components, and incorporated unit by unit in a device such as a vehicle. The module units contain module controllers for controlling the respective modules. The module controllers have storage means for storing detection data from state detection means of the modules, so that each module unit is able to perform data communication with the device controller.

[0011] As a result that the motor, fuel cell and battery are arranged as module units containing controllers, respectively, efficiency of assembling work and maintainability of modules are improved and control systems corresponding to the modules are integrated for the respective modules, thereby providing improved reliability of the control, easy parts replacement including that of the control system parts and improved applicability of modules with effective parts control.

[0012] In a preferred arrangement, this invention is characterized in that said device controller is adapted to perform bilateral data communication with said module controllers.

[0013] In this arrangement, data is stored in each module controller and the device controller can receive requisite data on request to the module controller, so that memory structure is simplified on the device controller side and effective control can be performed on the same communication line for each module.

[0014] In another preferred arrangement, this invention is characterized in that after a predetermined time has elapsed since the main switch was turned off, preparation processing is performed on said first or said second power supply source for the next operation.

[0015] In this arrangement, after a predetermined time has elapsed on the basis of a timer since operation was stopped and the main switch was turned off, the capacity of the power supply source is detected to be optimized sufficiently enough for normal operation, or when operation was stopped and the main switch was turned off, residual capacity of the first or the second power supply source is detected, capacity-up processing is performed at a time earlier than the time of the next driving schedule entered by the user by a length of time necessary to increase the detected residual electric capacity up to an optimum value, so that the device can be held on standby in an optimum condition that operation can be started stably and reliably at the time of next running for continuation of normal operation.

[0016] In addition, in order to achieve the second object, this invention may provide a hybrid-driven mobile body with a first and a second power supply source as power sources of a power system for driving the mobile body, wherein an available amount of power supply by each of said first and said second power supply source is detected, and a program is provided for calculating an expected travel distance of the mobile body from the available amount of power supply.

[0017] In this arrangement, since during travel operation, the available amount of power supply of each of the first and the second power source constituting the hybrid device, for example, residual capacity or residual fuel, is detected and the expected travel distance of the mobile body is calculated on the basis of the detected data, stable operation to the destination is verified and a prompt action can be taken when the expected travel distance or the residual quantity is insufficient.

[0018] In a preferred arrangement, this invention is

characterized in that said first power source is a fuel cell and said second one a battery; the fuel consumption ratio of the fuel cell and the capacity consumption ratio of the battery are calculated, and the expected travel distance of the mobile body is calculated on the basis of these consumption ratios; and if said residual fuel of the fuel cell and said residual capacity of the battery are not more than the respective predetermined setting values, warning is indicated.

[0019] In this arrangement, the hybrid power source is constituted by a fuel cell and a battery (secondary battery); the fuel consumption ratio of the fuel cell is calculated from the traveled distance and the fuel consumption; and the expected travel distance by the fuel cell is calculated from the fuel consumption ratio and the residual amount of fuel. Further, the capacity consumption ratio of the battery is calculated from the traveled distance and the voltage drop of the battery or the capacity consumption of the whole mobile body, and the expected travel distance is calculated from the capacity consumption ratio and the residual capacity. In this case, if the residual fuel and the residual capacity of the battery are not more than the respective predetermined values, warning is indicated and appropriate measures can be taken such as refueling and battery change, or charging.

[0020] In still another preferred arrangement, this invention is characterized in that the characteristic data of capacity corresponding to the current and voltage of the battery is provided beforehand, and the battery capacity is calculated from the detection data on the current or voltage of the battery, based on the characteristic data of capacity.

[0021] In this arrangement, the characteristic data of capacity corresponding to the current and voltage of the battery is stored beforehand in a ROM, etc, and when the current or voltage of the battery is detected, the battery capacity (residual capacity) at the time of detection is calculated from the stored characteristic data of capacity, based on the detection data.

[0022] In another preferred arrangement, this invention is characterized in that after a predetermined time has elapsed since a first detection data was obtained on said current or voltage, a second detection data is obtained on the current or voltage, and the impedance is calculated from the calculated capacity value based on the first and the second detection data.

[0023] In this arrangement, after a predetermined time has elapsed since the battery capacity and the impedance were calculated on the basis of the first detection data, the capacity and the impedance are calculated on the basis of the second detection data, and the state of deterioration of the battery is identified from the impedance change. Taking account of this impedance change, the expected travel distance can be calculated on basis of the residual capacity of the battery.

[0024] Further, in order to achieve the third object, this invention may provide a hybrid-driven device having a first and a second power supply source as power source-

es of a power system for driving the device, said first and second power supply sources being connected to said power system through switching means, respectively, and a device controller for controlling the device according to the operating conditions, wherein said first and second power supply sources have controllers, respectively; the controllers are adapted to detect abnormalities of the power supply sources and to store the detection data on abnormality; and said device controller is adapted to perform bilateral communication with the controllers of the power supply sources to send/receive data or commands, and to cut off the power supply source from said power system through said switching means when said device controller receives said detection data on abnormality.

[0025] In this arrangement, the device controller which controls the whole device is adapted to perform data communication with controllers of the power supply sources, and if abnormality happens in any of the power supply sources and the abnormality is detected by its controller, the detection data is sent to the device controller, and the device controller determines which supply source the abnormality happens in, and cuts off the abnormal power supply source from the power system through switching means such as a relay. Thus, the use of the abnormal power source is stopped promptly and operation is continued using the other power source while an appropriate action is taken against the abnormality, thereby minimizing damage.

[0026] The abnormality of the power supply source is detected such that the temperature and current or voltage of each power supply source are detected and it is determined to be abnormal when these values exceed the respective proper ranges. If such an abnormal state is detected, the detection data on abnormality is stored in the controller of the abnormal power source and sent from the controller to the device controller on request.

[0027] In a preferred arrangement, this invention is characterized in that the controller of each power supply source sends to said device controller a request signal for stoppage of discharging of the power supply source upon detection of abnormality of the power supply source, and when receiving the request signal, said device controller cuts off the power supply source from said power system through said switching means.

[0028] In this arrangement, the controller of each power supply source sends a signal requesting stoppage of discharging to stop the use of the power source upon detection of abnormality of the power source. The device controller which received the request signal for stoppage of discharging determines which power source the signal was sent from, and cuts off the power source from the power system through switching means. Thus, when abnormality happens in a power source, a command can be requested of stopping the use of the power source, from the abnormal power source side, using communication means between the controllers of the power sources and the device controller,

providing a prompter action to cope with the abnormality. The request signal for stoppage of discharging may be simply the detection data on abnormality. In this case, if abnormality is detected, the detection signal is sent to the device controller, and the device controller cuts off the abnormal power source accordingly.

Brief Description of the Drawings

[0029]

Fig. 1 is a view of external appearance of a hybrid-driven vehicle according to an embodiment of this invention;

Fig. 2 shows structural views of a hybrid-driven vehicle according to another embodiment of this invention;

Fig. 3 is block diagram of the control system of the hybrid-driven vehicle according to the embodiment of this invention;

Fig. 4 is a structural diagram of a portion of a fuel cell unit according to this invention;

Fig. 5 is a structural diagram of the power source control system according to this invention;

Fig. 6 is an illustration of the control system of the hybrid-driven vehicle according to this invention;

Fig. 7 is a flowchart of operations during standby of the hybrid-driven vehicle according to this invention;

Fig. 8 is a flowchart of detection and calculation of the state of the power source in the hybrid-driven vehicle according to this invention;

Fig. 9 is a flowchart of detection and its indication of the residual quantities of the power sources during running of the hybrid-driven vehicle according to this invention;

Fig. 10 is a flowchart of capacity control of the battery during running of the hybrid-driven vehicle according to this invention; and

Fig. 11 is a graph of the capacity characteristics (percentage to the maximum capacity) corresponding to the current (I) and voltage (V) of the battery.

Best Mode for Carrying out the Invention

Now, an embodiment of this invention will be described below with reference to the drawings.

[0031] Fig. 1 is a general structural view of a hybrid-driven vehicle according to an embodiment of this invention. The hybrid-driven vehicle 1 of this embodiment is applied to a motor bicycle. The hybrid-driven vehicle 1 is provided with a hybrid-driven system 2. The hybrid-driven system 2 comprises an electric motor unit 3, a transmission 4, a vehicle controller 5, a battery unit 6 and a fuel cell unit 7.

[0032] A fuel cell unit 7 comprised mainly of a fuel cell and a reformer, is disposed rearwardly of a seat 8 and upwardly of a drive wheel 9. In front of the seat 8 and

between the seat and a front fork 12 for steering a steering wheel 11, is disposed a methanol tank 13. The methanol tank 13 is provided with a filler cap 14.

[0033] The hybrid system comprised of a fuel cell in the fuel cell unit 7 and a battery in the battery unit 6 is adapted to drive an electric motor in the electric motor unit 3 to rotate the drive wheel 9.

[0034] Fig. 2(A) is a view of an example of another type of hybrid-driven motor bicycle, and Fig. 2(B) is a structural view of a hydrogen supplying device for the fuel cell.

[0035] The hybrid-driven vehicle 1 has a vehicle controller 5 and a battery unit 6 under a seat 8; under an vehicle controller 5 is provided an electric motor unit 3; and in front thereof is provided a fuel cell unit 7 comprised mainly of a fuel cell. On a carrier to the rear of the seat 8 is provided a hydrogen supplying device 15 for supplying hydrogen for power generation to the fuel cell unit 7.

[0036] The hydrogen supplying device 15, as shown in Fig. 2(B), is provided with a hydrogen bomb 16 together with a methanol tank 13, and with a fan 17 and a burner 18 for supplying combustion air, and further with a reformer 19 for producing hydrogen through catalyst, with primary fuel being heated and vaporized.

[0037] Fig. 3 is a schematic block diagram of the hybrid-driven vehicle according to this invention.

[0038] The hybrid-driven vehicle 1 is provided with a main switch SW1, a seat 8, a stand 20, a foot rest 21, an acceleration grip 22, a brake 23, an indicator 24, a lamp unit 25 including a light, a winker, etc, a user input device 26, a non-volatile memory 27 and a timer 28, and further with an electric motor unit 3, a transmission 4, a vehicle controller 5, a battery unit 6 and a fuel cell unit 7.

[0039] ON/OFF signals are sent from the main switch SW1 to the vehicle controller 5 to drive the motor-powered vehicle. To the seat 8, stand 20, foot rest 21 and brake 23 are fitted sensors S1-S4, respectively, and ON/OFF signals corresponding to seating/non-seating, use/non-use of the stand, feet-resting/non feet-resting and ON/OFF of the brake are sent from the respective sensors S1-S4 to the vehicle controller 5, where the respective operating conditions are detected.

[0040] The accelerator grip 22 constitutes output setting means, and to the accelerator grip 22 is fitted an accelerator opening sensor S5, from which signals of accelerator opening are sent to the vehicle controller 5 through gripping manipulation of the user. The electric motor is controlled according to accelerator opening. The vehicle controller 5 constitutes control means for controlling the output of the electric motor based on the output setting value from the output setting means constituted by the accelerator grip 22.

[0041] The user is able to input various data from a user input device 26 to the vehicle controller 5 to change, for example, the operating characteristics of the vehicle. Also, data are transferred between the non-volatile memory 27 and timer 28 and the vehicle controller

5, that is, to the non-volatile memory 27 is stored the information on the operating conditions of the vehicle at the time of stoppage, and the vehicle controller 5 reads the information on the stored operating conditions for control when operation is started.

[0042] The indicator 24 is driven by indicator-ON/OFF signals from the vehicle controller 5 and the operating conditions of the motor-powered vehicle are indicated on the indicator 24. The lamp unit 25 including a light, winker, etc is comprised of lamps 25b of the light, winker, etc. Activation-ON/OFF signals from the vehicle controller 5 drive a DC/DC converter 25a to light the lamps 25b.

[0043] The electric motor unit 3 is provided with a motor driver 30, an electric motor 31 connected to the drive wheel 9, an encoder 32, a regenerative current sensor S11 and regenerative energy control means 33. The motor driver 30 controls the electric motor 31 through duty signals from the vehicle controller 5, and the drive wheel 9 is driven by the output of the electric motor 31. The encoder 32 detects the position of the magnetic poles and the number of revolution of the electric motor 31. Information on the motor speed from the encoder 32 is stored in a memory in the motor driver 30 to be sent to the vehicle controller 5 as required. Output of the electric motor 31 is changed in its speed by the transmission 4 to drive the drive wheel 9, and the transmission 4 is controlled by speed-change command signals from the vehicle controller 5. The electric motor 31 is provided with a motor voltage sensor or a motor current sensor S7, and information on the voltage and current of the motor is stored in a memory in the motor driver to be sent to the vehicle controller 5 as required.

[0044] The battery unit 6 is provided with a battery 60, a battery controller 61 and a battery relay 62. The fuel cell unit 7 is provided with a fuel cell 70 constituting power generating means, a fuel cell controller 71, a reverse current prevention element 72 and a fuel cell relay 73. There provided are a first power supply path L1 allowing supply of the output current from the fuel cell 70 to the battery 60 and a second power supply path L2 allowing supply of the output current from the battery 60 to the electric motor 31, and electric power is supplied through an electric power regulating section 80.

[0045] The battery controller 61 is provided with detection means for detecting the charging state of the battery 60, and the detection means is comprised of a battery temperature sensor S12, a battery voltage sensor S13 and a battery current sensor S14, and information from these sensors is stored in a memory in the battery controller 61 to be entered in the vehicle controller 5 as required. The battery relay 62 is activated by ON/OFF signals from the vehicle controller 5 to control electric power supply from the second power supply path L2.

[0046] Communication data are sent from the vehicle controller 5 to the fuel cell controller 71, and the fuel cell controller 71 controls the fuel cell 70 on the basis of these data. The fuel cell controller 71 is provided with detection means for detecting the state of the fuel cell

70. The detection means is comprised of various temperature sensors S21, a fuel cell voltage sensor S22 and a fuel cell current sensor S23, and information from these sensors is stored in a memory in the fuel cell controller 71 to be entered in the vehicle controller 5 as required. The fuel cell relay 73 connected to the fuel cell controller through rectifier diode (reverse current prevention element) 72 is activated by ON/OFF signals from the vehicle controller 5 to control electric power supply from the first power supply path L1.


[0047] Fig. 4 is a structural diagram of a portion of a fuel cell according to an embodiment of this invention.

[0048] The fuel cell unit 7 in this embodiment comprises a methanol tank 102, a reformer 103, a shift converter 104, a selective oxidation reactor 105, a fuel cell 70, a moisture collecting heat exchanger 107, a water tank 108 and a fuel cell battery controller 71. The fuel cell controller 71 is connected to the devices such as valves, pumps and fans, and sensors. The reformer 103, shift converter 104, selective oxidation reactor 105 and fuel cell 70 are provided with temperature sensors Tr, Tb, Ts, Tp, Tc, and the temperature of these components is controlled properly by the fuel cell battery controller 71 (Fig. 3) through temperature detection.


[0049] The reformer 103 is provided with a burner 110, an evaporator 111 and a catalyst layer 112. To the burner 110 is supplied methanol from the methanol tank 102 by a burner pump 113 activated through temperature detection by the temperature sensor Tb, and air by a burner fan 114, and the evaporator 111 is heated by combustion action of the mixture. The double circle in the figure represents an air inlet. To the evaporator 111 is supplied methanol fed from the methanol tank 102 by the methanol pump 115, and water fed from the water tank 108 by the water pump 116, with methanol and water mixed together. The burner 110 heats the evaporator 111 to vaporize the fuel mixture of methanol and water, and the vaporized fuel mixture in the evaporator 111 is supplied to the catalyst layer 112.

[0050] To the burner 110 is supplied surplus (or bypassing) hydrogen from the fuel cell 70 through a line 201 for combustion. The combustion heat of the burner 110 vaporizes primary fuel (raw material) composed of methanol and water, and heats the catalyst layer 112 to maintain its temperature at a value required for catalytic reaction. Combustion gas, and air not involved in the reaction are discharged to the outside through an exhaust passage 202.

[0051] The catalyst layer 112 is made, for example, of Cu-base catalyst, and resolves the mixture of methanol and water into hydrogen and carbon dioxide at a catalyst reaction temperature of about 300 °C as follows:




[0052] In the catalyst layer, a very small amount (about 1%) of carbon monoxide is produced:




[0053] Since this CO is adsorbed by catalyst in the cell 70 and lowers electromotive force reaction, its concentration is lowered in the shift converter 104 and the selective oxidation reactor 105 on the latter stage, and in the cell 70, to the order of one thousand to some tens of ppm.

[0054] In the shift converter 104, carbon monoxide in the resolved gas is turned to CO₂ at a reaction temperature of about 200 °C in the following chemical reaction by surplus water vapor:



and CO concentration is lowered to the order of about 0.1%.

[0055] In the selective oxidation reactor 105, CO is further changed chemically to CO₂ at a catalyst temperature of about 120 °C using platinum-base catalyst in the oxidation reaction as:



and its concentration is reduced further to 1/10 of the previous value or smaller. Thus, the CO concentration in the cell 70 can be lowered to the order of some tens of ppm.

[0056] The reformer 103 allows raw material to be reformed so as to produce hydrogen as described above, and the hydrogen acquired is supplied to the fuel cell 70 through the shift converter 104 and the selective oxidation reactor 105. Between the reformer 103 and the shift converter 104 are provided a buffer tank 117 for absorbing pulsation and pressure change and switching valves 117a, 117b, and the hydrogen is returned to the burner 110 through activation of these switching valves 117a, 117b. The shift converter 104 is cooled by a cooling fan 118 after temperature detection by the temperature sensor Ts. Cooling air is discharged to the outside through an exhaust passage 203.

[0057] Between the shift converter 104 and the selective oxidation reactor 105 are provided a buffer tank 124 and switching valves 124a, 124b, and hydrogen is returned to the burner 110 through activation of these switching valves.

[0058] Hydrogen sent from the shift converter 104 is mixed with air fed by a reaction air pump 119 to be supplied to the selective oxidation reactor 105. The selective oxidation reactor 105 is cooled by a cooling fan 120 after temperature detection by the temperature sensor Tp. The cooling air is discharged to the outside through an exhaust passage 204.

[0059] Between the selective oxidation reactor 105 and the fuel cell 70 are provided a buffer tank 121 and

switching valves 121a, 1241, and hydrogen is returned to the burner 110 in the reformer 103 through activation of these switching valves.

[0060] As a result of flow control of the switching valves 1171, 117b to the shift converter 104, that of the switching valves 124a, 124b to the selective oxidation reactor 105 and that of the switching valves 121a, 121b to the fuel cell 70, the amount of hydrogen supplied to the fuel cell 70 can be regulated for electromotive force control. Excessive oxygen is supplied in this case, so that the electromotive force is controlled according to the amount of hydrogen.

[0061] Such an electromotive force control is performed as follows: required electromotive force is calculated by the vehicle controller 5 based on the data from sensors S21-S23 and the detected data on the operating conditions from other various sensors, the flow rate of each switching valve is calculated by the vehicle controller 5 or the fuel cell controller 71 based on the calculation results, taking account of the time lag required for the hydrogen quantity in the cell to be changed after activation of the switching valve, on the basis of which ON/OFF control or opening control of each switching valve is performed by the fuel cell controller 71. In this case, a larger supply quantity of the primary fuel such as methanol may increase the amount of evaporation of hydrogen to thereby increase the electromotive force, in which case time lag is produced by the time hydrogen is increased in quantity enough to participate in power generation. Such a time lag is compensated for by the electric power from the battery.

[0062] To the fuel cell 70 is supplied water from the water tank 108 by a cooling and humidifying pump 122, and air is supplied from the moisture collection heat exchanger 107 by a pressurizing air pump 123 through temperature detection of the temperature sensor Tc. Using the water, air and hydrogen, power generation is performed in the fuel cell 70, as described below.

[0063] The fuel cell 70 is configured such that electrodes are each formed with, for example, a platinum-base porous catalyst layer (not shown) provided on both sides of a cell film (not shown) with a cooling and humidifying water passage 205 formed therein. To one electrode is supplied hydrogen from the selective oxidation reactor 105 through a hydrogen passage 206, and to the other electrode, oxygen (air) through an oxygen passage 207. Hydrogen ions move from the hydrogen passage 205 of the hydrogen side electrode to the oxygen side electrode through the cell film and are combined with oxygen to form water. The migration of electrons (-) associated with the migration of the hydrogen ions (+) allows the electromotive force to be generated between the electrodes.

[0064] This electromotive force generation is a heat development reaction, and for the purpose of cooling and smooth migration of hydrogen ions to the oxygen side electrode, water is supplied from the water tank 108 to the water passage 205 in the cell film between both

electrodes by the pump 122. The water which has passed through the water passage 205 and increase in temperature, exchanges heat with air in the heat exchanger 107 and returns to the water tank 108. The water tank 108 is provided with a radiation fins 208 for cooling water. Numeral 209 designates an overflow pipe.

[0065] Air is introduced to the heat exchanger 107. The air, after exchanging heat with water at an elevated temperature, is changed to a hot air, and supplied to the oxygen passage 207 by the air pump 123. As a result of the hot air being supplied, combining reaction with hydrogen ions is accelerated, providing effective electromotive force reaction. Therefore, an air inlet (shown in the figure by a double circle) is preferably provided in the vicinity of the selective oxidation reactor 105 or the catalyst layer 112 where the foregoing high temperature catalytic reaction takes place.

[0066] Oxygen in the air passing through the oxygen passage 207 and combined with hydrogen ions is turned into water and collected in the water tank 108. The surplus air (oxygen and nitrogen) is discharged to the outside through an exhaust passage 210.

[0067] Water used in the fuel cell 70 and water produced by power generation as described above, exchange heat with cooling air in the moisture collecting heat exchanger 107 and is returned to the water tank 108. Also, the surplus hydrogen used for power generation in the fuel cell 70 is returned to the burner 110 of the reformer 103 through a valve 211 and a line 201.

[0068] As described above, in the fuel cell unit 7, by means of the reformer 103 in which the evaporator 111 is heated by the burner 110 and raw material vaporized by the evaporator 111 is supplied to the catalyst layer 112, the raw material is reformed to produce hydrogen, and the hydrogen acquired is supplied to the fuel cell 70 through the shift converter 104 and the selective oxidation reactor 105 for power generation. In this case, hydrogen acquired from the selective oxygen reactor 105 may be stored, as shown in Fig. 2(B), temporarily in the hydrogen bomb 16.

[0069] The output of the fuel cell 70, as shown in Fig. 3, is connected to the power regulating section 80 through the reverse current prevention element 72 and the fuel cell battery relay 73, and the power regulating section 80 is connected to the battery 60 and the electric motor 31.

[0070] Fig. 5 is a block diagram of the power source control system of the hybrid-driven vehicle according to this invention.

[0071] The vehicle controller 5 is connected to the electric motor unit 3, battery unit 6 and fuel cell unit 7 through bilateral communication lines 220, 221, 222, respectively. The fuel cell unit 7 is connected to the electric motor unit 3 through (+) side current line 223a and (-) side current line 223b. On the (+) side current line 223a is provided a switch 225. This switch 225 is turned ON and OFF by the vehicle controller 5.

[0072] The battery unit 6 is connected to the electric

motor unit 3 through the (+) side current line 223a and the (-) side current line 223b which are coupled to the (+) side current line 224a and (-) side current line 224b, respectively. On the (+) side current line 224a is provided a switch 226. This switch 226 is turned ON and OFF by the vehicle controller 5.

[0073] The electric motor unit 3 is a unit in which a controller (motor driver 30), an encoder and sensors, as well as an electric motor 31 (Fig. 3), are integrated together as a module. Such an electric motor unit 3 can be mounted detachably on a vehicle as a unitary component. Therefore, the bilateral communication line 220 and the current lines 223a, 223b, 224a, 224b are each connected to the motor driver 30 as a controller of the electric motor unit 3 through the respective couplers (not shown).

[0074] The motor driver 30 has a memory, and detected data such as the operating conditions of the electric motor unit 3 (for example, number of revolution), throttle opening, running speed, request load, temperature and shift position are sent to the vehicle controller 5 to update the memory in the vehicle controller 5 for storage.

[0075] The battery unit 6 is a unit in which a battery controller 61, sensors S12-S14 and a relay 52, as well as a battery 60 as shown in Fig. 3, are integrated together as a module. Such a battery unit 6 can be mounted detachably on a vehicle as a unitary component. Therefore, the bilateral communication line 221 and the current lines 224a, 224b are connected to the battery controller 61 of the battery unit 6 through couplers (not shown).

[0076] The battery controller 61 has a memory, to which are stored the data on the battery unit conditions such as temperature, voltage and current, and the residual capacity of the battery 60 while updated constantly. Thus, the data can be transferred through bilateral communication between the battery controller and the vehicle controller to supply required power during running, and when the battery 60 is replaced, the residual capacity can be immediately recognized by the vehicle controller for processing of expected travel distance, etc.

[0077] The fuel cell unit 7 is a unit in which a fuel cell controller 71, sensors S21-S23 (Fig. 3) and a relay 52, as well as the fuel cell 70, reformer, etc, are integrated together as a module. Such a fuel cell unit 7 can be mounted detachably on a vehicle as a unitary component. Therefore, the bilateral communication line 222 and the current lines 223a, 223b are connected to the fuel cell controller 71 of the fuel cell unit 7 through couplers (not shown).

[0078] The fuel cell controller 71 has a memory, to which are stored the data on the fuel cell unit conditions such as temperature, voltage and current, and the capacity (specifically, the residual fuel in the methanol tank) of the fuel cell while updated constantly. Thus, the data can be transferred through bilateral communication between the fuel cell controller and the vehicle controller

to supply required power during running, and processing of expected travel distance, etc, can be performed.

[0079] Although in the embodiment in Fig. 5, a fuel cell and a battery are used as two power supply sources constituting the hybrid-driven vehicle, two fuel cells or two batteries (second batteries) may be used, or an engine type generator or a capacitor may be used. In addition, this invention can be applied to watercrafts or other devices in addition to vehicles.

[0080] Fig. 6 is an illustration of data communication in the control system of the hybrid-driven vehicle according to this invention.

[0081] The vehicle controller 5 transmits, to the electric motor unit 3 (motor driver (controller of the electric motor) 30, encoder 32 and other sensor group), battery controller 61 and fuel cell controller 71, request signals of various data stored in the memories of the controllers. Upon this data request, required data are sent back to the vehicle controller 5 from the sensor group of the electric motor unit 3, and the controllers 30, 61, 71. The contents of the data include state information such as temperature, voltage, current, error information and capacity, and control information such as output request.

[0082] In this case, the vehicle controller 5 calculates, on the basis of the data from the sensor group and the controllers 30, 61, 71, the optimum amount of drive to the units, and the data on the amount of drive are sent, as operation command data, to the motor driver 30 and controllers 30, 61, 71 for the control of the electric motor unit 3, battery unit 6 and fuel cell unit 7.

[0083] In such a bilateral data communication, according to this invention, when abnormality happens in the battery unit 6 or the fuel cell unit 7, the abnormality is detected by the battery controller 61 or the fuel cell controller 71, and the detection data on abnormality is sent to the vehicle controller 5. The vehicle controller 5 determines accordingly whether the abnormality happens in the battery unit 6 or the fuel cell unit 7, and cuts off the switch 225 or 226 (Fig. 5) of the power source where the abnormality is detected, to stop power supply from the abnormal power source to the motor. The switches 225, 226 correspond to the fuel cell relay 73 and the battery relay 62 of Fig. 3, respectively. The battery unit 6 is determined to be abnormal when the detection value of any of the battery temperature sensor S12, battery voltage sensor S13 and battery current sensor S14 is excessively large or small beyond the range of normal detection values, and this detection value is stored as detection data on abnormality in the memory of the battery controller 61.

[0084] Similarly, the fuel cell unit 7 is determined to be abnormal when the detection value of any of the temperature sensor S21, fuel cell voltage sensor S22 and fuel cell current sensor S23 is excessively large or small beyond the range of normal detection values, and this detection value is stored as detection data on abnormality in the memory of the fuel cell controller 71.

[0085] The vehicle controller 5 constantly sends to the

controllers 61, 71 data requests including the detection data on abnormality, and if an abnormal state exists, the data is sent back to the vehicle controller 5. When the vehicle controller receives the detection data on abnormality, connection between the power source and the motor is cut off as described above.

[0086] If abnormality is detected, the battery controller 61 or the fuel cell controller 71 that has detected the abnormality, may send a request signal for stoppage of discharging of the abnormal battery or the fuel cell, to stop the use of the battery or the fuel cell. The vehicle controller 5 that has received the request signal for stoppage of discharging, determines whether the battery or the fuel cell needs to stop discharging, and cuts off the switch 225 or 226 of the abnormal power source to stop the use of the power source.

[0087] Such a bilateral communication of the detection data on abnormality allows a prompt action against abnormality at the time of occurrence of abnormality in the power source. In this case, even if the failure of the sensor itself is detected as abnormality of the power source, it can be handled as an abnormal state.

[0088] Fig. 7 is a flowchart of control of the power supply system during non-running of the hybrid-driven vehicle according to this invention.

[0089] The operation at each step is as follows:

S101: It is detected whether or not the main switch for power supply to the vehicle is OFF, to determine the end of use of the vehicle. If the vehicle is in use (in the state of running), necessary data communication is performed between the vehicle controller and each controller of the fuel cell unit and the battery unit, as shown previously in Fig. 6, for drive control of the vehicle according to the control program during running.

S101-A: a setting value of the timer count is determined from the time of the next running and the current residual amount. That is, if the main switch is OFF, the timer is operated, and the need of discharging or charging is determined from the current battery capacity. Further, a length of time is calculated necessary for discharging or charging operation, a setting time is determined such that it is earlier than the time of the next running by the foregoing necessary length of time plus a margin (for example, a few to some tens of minutes), and the time difference between the time of switching-off of the main switch and that setting time is calculated as a setting value.

S102: If the main switch is OFF, an end signal is sent from the vehicle controller to each controller of the motor unit, fuel cell unit and battery unit.

S103: The elapsed time after switching-off of the main switch is counted by the timer.

S104: It is determined whether or not the elapsed time is a given setting value (the value calculated at Step S101-A). If it is less than the setting value,

counting is continued till the setting value is reached.

S105: After a given setting time has elapsed since switching-off of the main switch, the capacity of the fuel cell and the battery is detected. In this case, residual fuel in the methanol tank is detected for the fuel cell.

S106: The detected battery capacity is compared with a given setting value A. The setting value A is set to a minimum capacity required for smooth starting of the next running.

S107: If the battery capacity is not larger than the setting value A, the fuel cell unit is operated through the fuel cell controller, to charge the battery so that the capacity becomes larger than the setting value A.

S108: If the battery capacity is larger than the setting value A, the battery capacity is compared with a given setting value B.

S109: If the battery capacity is larger than the setting value B, a discharging command is sent to the battery controller, and the battery is discharged till the capacity reaches the setting value B.

S110: If the battery capacity is not larger than the setting value B (larger than the setting value A), the fuel cell and the battery is held on standby for starting of the next running.

As described in Fig. 6, the vehicle controller 5 transmits or receives several kinds of data to or from the battery controller 61 and the fuel cell controller 71.

S111: The data on the traveled distance from the start of running is obtained. The data, which is detected by a distance detection sensor located on the axle, is written in a RAM (or non-volatile memory) of the battery controller or the fuel cell controller, or in a RAM (or non-volatile memory) provided in the vehicle controller, for reading.

S112: The fuel consumption ratio is calculated on the basis of the data on the quantity of methanol fuel consumed from the start (difference between the current residual fuel in the methanol tank and the residual fuel at the start of operation) and the data on the traveled distance. This fuel consumption ratio is used to calculate the expected travel distance by the fuel cell.

S113: The capacity consumption ratio for the whole vehicle is calculated on the basis of the battery capacity data (the current battery capacity) and the traveled distance. This capacity consumption ratio is used to calculate the expected travel distance from the residual battery capacity and residual methanol.

For example, the expected travel distance may be calculated by obtaining the data on the capacity consumption of the whole vehicle including the fuel consumption and the battery consumption, and calculating the capacity consumption ratio of the vehicle from this capacity consumption and the traveled

distance.

For example, if the consumption ratio of the electric power supplier (fuel cell) is 100cc/Ah and the capacity consumption ratio is 2.0 km/Ah, the expected travel distance in the case of the residual fuel of 3000 cc and the residual battery capacity of 5.0 A/h is:

$$(3000/100+5.0) \times 2.0 = 70 \text{ km.}$$

S114: It is determined whether the residual methanol fuel in the fuel tank is not more than a given setting value.

S115: If the amount of methanol fuel is more than the given setting value, the residual quantity is displayed on a fuel indicator panel as usual.

S116: If the amount of methanol fuel is not more than the given setting value, it is determined whether the residual battery capacity is not more than the given setting value. If more than the setting value, then at S115, the residual battery capacity is displayed on the indicator panel as usual, as well as the amount of the methanol fuel.

S117: If the residual quantity of the methanol fuel or the battery is not more than the respective given setting value, warning is indicated on the indicator panel.

S118: If the amount of fuel detected at S114 exceeds the setting value, it is determined whether the residual battery capacity is not more than the given setting value. If it is not more than the setting value, warning is indicated (Step S117), and if it is more than the setting value, the residual quantity is indicated as usual (Step S115).

Fig. 10 is a flowchart of control of the battery capacity during running. Fig. 11 is a graph of the capacity characteristics (percentage to the maximum capacity) corresponding to the current (I) and voltage (V) of the battery.

As described above, the vehicle controller 5 performs bilateral data communication with the battery controller 61.

S121: The first detection data on the voltage and/or current of the battery is read from the battery controller to be sent to the vehicle controller. The vehicle controller stores the data on the capacity characteristics of Fig. 11, as a map beforehand in a ROM, etc. From the voltage or current data, the degree of consumption (percentage to the maximum capacity) of the battery capacity at the time is found from the map in the graph of the capacity characteristics. This battery capacity changes, for example, with a certain time of use, as shown in the figure by the arrow.

S122: After the first data on the current and voltage is obtained, the timer begins counting.

S123: It is determined by the timer whether or not

the given setting time is reached. Timer counting is continued till the setting time is reached.

S124: After the setting time has elapsed, the second data on the current and/or voltage of the battery is read from the battery controller to be sent to the vehicle controller.

S125: The degree of consumption of the battery capacity is found from the graph of Fig. 11, based on the foregoing first data and the second data, and the impedance is calculated. The deterioration of the battery is determined from the impedance change.

[0090] Alternatively, during use of the battery, the current and voltage may be detected in an approximately constant current state generated by quick change over of the battery switch (FET, etc), and the residual battery capacity and the impedance may be calculated from the current and voltage characteristics in this constant current state.

Industrial Applicability

[0091] According to this embodiment as described above, as a result that the motor, fuel cell and battery are arranged as module units containing controllers, respectively, efficiency of assembling work and maintainability of modules are improved and control systems corresponding to the modules are integrated for the respective modules, thereby providing improved reliability of the control, easy parts replacement including that of the control system parts and improved applicability of modules with effective parts control.

[0092] In addition, if the device (vehicle) controller which controls the whole device is adapted to perform bilateral data communication with the module controllers such as the motor, battery and fuel cell, then data is stored in each module controller and the device controller can receive requisite data on request to the module controller, so that memory structure is simplified on the device controller side, and effective control can be performed on the same communication line for each module.

[0093] Further, if after a predetermined time has elapsed since the main switch was turned off, preparation processing is performed on the power supply sources such as the fuel cell and the battery, for the next operation, then after a predetermined time has elapsed on the basis of a timer since operation was stopped and the main switch was turned off, the capacity of the fuel cell or the battery is detected to be optimized sufficiently enough for normal operation, so that the device can be held on standby in an optimum condition that operation can be started stably and reliably at the time of next running, for continuation of normal operation.

[0094] Furthermore, since during travel operation, the available amount of power supply of each of the first and the second power source constituting the hybrid device,

for example, residual capacity or residual fuel, is detected and the expected travel distance of the mobile body is calculated on the basis of the detected data, stable operation to the destination is verified and a prompt action can be taken when the expected travel distance or the residual quantity is insufficient.

[0095] Moreover, the use of the abnormal power source is stopped promptly and operation is continued using the other power source while an appropriate action is taken against the abnormality, thereby minimizing damage.

Claims

1. A hybrid-driven device having a first and a second power supply source as power sources for a power system for driving the device, a main switch for switching on the power sources, and a device controller for controlling the device, **characterized in that** said power system and said first and second power supply sources are arranged as module units, respectively, each module unit is provided with a module controller and detection means for detecting the state of the module, and said module controller has storage means for storing detected state data.
2. The hybrid-driven device as set forth in claim 1, wherein said device controller is adapted to perform bilateral data communication with said module controllers.
3. The hybrid-driven device as set forth in claim 1 or 2, wherein after a predetermined time has elapsed since the main switch was turned off, preparation processing is performed on said first or said second power supply source for the next operation.
4. A hybrid-driven mobile body with a first and a second power supply source as power sources of a power system for driving the mobile body, **characterized in that** an available amount of power supply by each of said first and said second power supply source is detected, and a program is provided for calculating an expected travel distance of the mobile body from the available amount of power supply.
5. The hybrid-driven mobile body as set forth in claim 4, wherein said first power source is a fuel cell and said second one a battery; the fuel consumption ratio of the fuel cell and the capacity consumption ratio of the battery are calculated, and the expected travel distance of the mobile body is calculated on the basis of these consumption ratios; and if said residual fuel of the fuel cell and said residual capacity of the battery are not more than the respective prede-

termined setting values, warning is indicated.

6. The hybrid-driven mobile body as set forth in claim 5, wherein the characteristic data of capacity corresponding to the current and voltage of the battery is provided beforehand, and the battery capacity is calculated from the detection data on the current or voltage of the battery, based on the characteristic data of capacity.
7. The hybrid-driven mobile body as set forth in claim 6, wherein after a predetermined time has elapsed since a first detection data was obtained on said current or voltage, a second detection data is obtained on the current or voltage, and the impedance is calculated from the calculated capacity value based on the first and the second detection data.
8. A hybrid-driven device having a first and a second power supply source as power sources of a power system for driving the device, said first and second power supply sources being connected to said power system through switching means, respectively, and a device controller for controlling the device according to the operating conditions, **characterized in that** said first and second power supply sources have controllers, respectively; the controllers are adapted to detect abnormalities of the power supply sources and to store the detection data on abnormality; and said device controller is adapted to perform bilateral communication with the controllers of the power supply sources to send/receive data or commands, and to cut off the power supply source from said power system through said switching means when said device controller receives said detection data on abnormality.
9. The hybrid-driven device as set forth in claim 8, wherein the controller of each power supply source sends to said device controller a request signal for stoppage of discharging of the power supply source upon detection on abnormality of the power supply source, and when receiving the request signal, said device controller cuts off the power supply source from said power system through said switching means.

FIG. 1






FIG. 2

(A)



(B) 15: Hydrogen supplying device 19: Reformer 13: Methanol tank






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10





FIG. 11



INTERNATIONAL SEARCH REPORT

International application No.

PCT/JP00/05660

A. CLASSIFICATION OF SUBJECT MATTER Int.Cl. ⁷ B60L11/18		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) Int.Cl. ⁷ B60L11/00-11/18		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	JP, 2-168802, A (Toyoda Automatic Loom Works, Ltd.), 28 June, 1990 (28.06.90) (Family: none)	1-9
A	JP, 3-284104, A (Fuji Electric Co., Ltd.), 13 December, 1991 (13.12.91) (Family: none)	1-9
A	JP, 6-253409, A (Kabushiki Kaisha Aqueous Research), 09 September, 1994 (09.09.94) (Family: none)	1-9
A	US, 5780980, A (Hitachi, Ltd.), 14 July, 1998 (14.07.98) & JP, 8-289410, A	1-9
A	JP, 10-117406, A (Fuji Photo Film Co., Ltd.), 06 May, 1998 (06.05.98) (Family: none)	1-9
EA	JP, 2000-173675, A (YAZAKI CORPORATION), 23 June, 2000 (23.06.00) (Family: none)	1-9
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/> See patent family annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 01 November, 2000 (01.11.00)		Date of mailing of the international search report 14 November, 2000 (14.11.00)
Name and mailing address of the ISA/ Japanese Patent Office		Authorized officer
Facsimile No.		Telephone No.

Form PCT/ISA/210 (second sheet) (July 1992)